

SERA FREQUENCY UTILIZATION PLAN for 1240-1300 GHz

1240.00 - 1246.00	ATV #1
1246.00 - 1248.00	NBFM point to point links and digital duplex
1248.00 - 1258.00	Digital communications
1252.00 - 1258.00	ATV #2
1258.00 - 1260.00	NBFM point to point links and digital duplex
1260.00 - 1270.00	Satellite up links, experimental simplex ATV
1270.00 - 1276.00	FM Repeater inputs, 239 pairs, every 25 KHz
1271.00 - 1283.00	Non-coordinated test pair
1276.00 - 1282.00	ATV #3
1282.00 - 1288.00	FM Repeater outputs paired with 1270-1276
1288.00 - 1294.00	Wide Band experimental, simplex ATV
1294.00 - 1295.00	Narrow Band FM simplex, every 25 KHz
1294.50	National simplex calling channel
1295.00 - 1297.00	Narrow Band weak signal (No FM)
1295.00 - 1295.80	SSTV, FAX, ACSSB experimental
1295.00 - 1296.00	Reserved for EME, CW expansion
1296.00 - 1296.05	EME exclusive
1296.07 - 1296.08	CW Beacons
1296.10	CW, SSB Calling Frequency
1296.40 - 1296.60	Cross Band linear translator output
1296.80 - 1297.00	Experimental Beacons exclusive
1297.00 - 1300.00	Digital Communications

NOTE: This is the ARRL recommended 1.2 GHz band plan, SERA has not compiled their own individual proposal for this spectrum.

